

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



Figure 1 Airway ciliated cells and goblet cells observed with scanning electron microscope. Cilia on the surface of ciliated cell and secreted mucin from the goblet cells are clearly shown.




Figure 2 Airway epithelial cells in air-liquid interface and measuring device for their physiological properties (i.e. transcellular electrical resistance).




Figure 3 Transepithelial electrical resistance (Ohms cm²) across a monolayer of A549 cells grown on polyester membrane support.




Figure 4 Quinacrine stain was accumulated specifically inside mucin secretory granules of the airway goblet cells. Cells were stained in 100  $\mu$ M quinacrine for 5 minutes.




Figure 5 The concentration-dependence of UTP-induced mucin exocytosis in normal tracheal goblet cells. The concentration-dependence curves were reproduced in triplicate. The secretion of mucin was monitored with quinacrine fluorescence. Data were fit as a sigmoidal dose-response.




Figure 6 Ciliary beating frequency (CBF) calibration curve. The results from our CBF measurement system are similar to the results obtained from fast cinematography (standard method).




Figure 7 Cross-section SEM image of cylindrical nanopores formed  $p^{++}$  Si (Janshoff et al., 1998).






Figure 8 Porous size varies with applied current; p++ Si, HF (aq) : EtOH = 3:1 (Janshoff et al., 1998).




Figure 9 Patterned airway epithelial cell layers trapped on porous silicon support.




Figure 10 Schematic diagram for Incorporation of airway epithelial cell layers grown on porous silicon into microfluidic device or flow chamber.





Figure 11 Physiological parameters sensing device. This device is composed of gas or fluid perfusion path, media perfusion path, Snapwell, and four electrodes (Harvard Apparatus, Holliston, MA).